



Direct Fit Kit

TRV & lock shield valve pack designed for use with Myson LST radiators

Submittal Data Sheet

Provide **Myson Direct Fit Valve Kit** in quantities and locations specified per plan. Direct Fit Valve Kits shall be supplied as per **General Specifications** listed below and installed as per manufacturer's instructions. All Myson valves are covered by a 1-Year Limited Warranty.

This kit utilizes a head horizontal valve body fitted to the top connection of the radiator. The sensing head is connected to the valve body via an extension adaptor that allows the sensing head to project through the radiator enclosure. A Myson Matchmaster lockshield radiator valve is included in the kit for control of the water flow through the radiator.



This kit is suitable for TBOE connection only.

General Specifications

- * TRV Conformation to BS EN215-1
- * Maximum operating pressure 145 PSI
- * Maximum water temperature 248°F
- * Maximum differential pressure 8.7 PSI
- * Sensing element is liquid filled.
- * Hysteresis < 0.5°K
- * Finish is satin brass.
- * Controlling range 46.4 - 82.4°F.
- * Matchmaster L/S valve fully compliant with BS 2767-10.

The Myson Direct Fit Kit Components

- * Myson thermostatic sensing head.
- * Head horizontal TRV body
- * (15mm/1/2" BSP) Extension adaptor
- * Panel Bush
- * Myson Matchmaster L/S valve.